


- All the dimensions are shown in millimetres
- Horizontal tube dia 22mm
- Vertical tube dia 38mm
- Bracket length - 50mm
- Made from 304 Polished Stainless Steel
- ½ inch BSP underside tapings
- Test pressure: 10 Bar
- Max working temperature: 8 Bar
- Heat output - in accordance with EN 442

Please Note:

- Please allow minimum of 100mm for valves
- Summer element use will affect pipe centres.
- The flow and return can be reversed

| Premier XL Space | Water Content (L) | Weight (KG) | Pipe Centres +/- 2mm | Fixing Centres (H) +/- 2mm | Fixing Centres (W) +/- 2mm | Height (mm) | Width (mm) |
|------------------|-------------------|-------------|----------------------|----------------------------|----------------------------|-------------|------------|
| RXPS-0610538 | 2.1 | 3.2 | 500 | 468 | 500 | 610 | 538 |
| RXPS-1076538 | 3.8 | 6.1 | 500 | 624 | 500 | 1076 | 538 |
| RXPS-1700538 | 5.9 | 9.7 | 500 | 1248 | 500 | 1700 | 538 |

Installation:



- 1) Wall Plug
- 2) Wall Support
- 3) Grub Screw
- 4) Allen Key (Not Supplied)
- 5) Wall Screw
- 6) Solid Fixing Lug

Step 1: Select the desired mounting position, make sure the wall is adequate to take the fixing points of the rail i.e anchor points must be securely attached to a stud or masonry.

Step 2: Loosely screw the wall support (Part 2) into the wall using the wall screw (5) and washer. Use wall plug (1) if you are fixing into masonry. Do not tighten fully.

Step 3: Manoeuvre the rail back onto the bracket and tighten with the grub screw (3).

Cleaning:

- Do not use any abrasive or chemical cleaners to clean the radiators as this will cause damage to the surface finish. Please use warm water and a damp cloth.
- Do not clean when hot.