



- All the dimensions are shown in millimetres
- Tube dia 20mm x 20mm
- Header tube dia 30mm x 30mm
- Bracket length - 55-75mm
- ½ inch BSP bottom opposite end connections
- Test pressure: 10 Bar
- Max working temperature: 8 Bar
- Heat output - in accordance with EN 442

Please Note:

- Please allow minimum of 100mm for valves
- Summer Element use will affect pipe centres
- The flow and return can be reversed

| Premier Curved | Water Content (L) | Weight (KG) | Pipe Centres +/- 2mm | Fixing Centres (H) +/- 2mm | Fixing Centres (W) +/- 2mm | Height (mm) | Width (mm) |
|----------------|-------------------|-------------|----------------------|----------------------------|----------------------------|-------------|------------|
| RXPC- 0800500 | 3.6 | 6 | 450 | 624 | 350 | 800 | 500 |
| RXPC- 0800600 | 4.1 | 6.8 | 550 | 624 | 450 | 800 | 600 |
| RXPC- 1200500 | 5.4 | 8.9 | 450 | 1014 | 350 | 1200 | 500 |
| RXPC- 1200600 | 6.1 | 10.2 | 550 | 1014 | 450 | 1200 | 600 |
| RXPC- 1500500 | 6.7 | 12.2 | 450 | 1326 | 350 | 1500 | 500 |
| RXPC- 1500600 | 7.7 | 13.8 | 550 | 1326 | 450 | 1500 | 600 |
| RXPC- 1800500 | 8.2 | 13.5 | 450 | 1599 | 350 | 1800 | 500 |
| RXPC- 1800600 | 9.3 | 15.4 | 550 | 1599 | 450 | 1800 | 600 |

Installation:

